

All Terrain T/A KO2 - part number	Tire Size, Load Index &Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
64055	30x9.50R15/C 104S	Standard	RWL	//	6.5" - 8.5"	9.5" on 7.5"	29.5"	705	15.0	1990@50	39.68 lbs
69948	31x10.50R15/C 109S	Standard	RWL	//	7" - 9"	10.6" on 8.5"	30.5"	682	15.0	2270@50	44.64 lbs
13079	32x11.50R15/C 113R	Standard	RWL	//	8" - 10"	11.4" on 9"	31.5"	659	15.0	2535@50	49.18 lbs
11548	33x10.50R15/C 114R	Standard	RWL	//	7" - 9"	10.6" on 8.5"	32.5"	640	15.0	2600@50	51.06 lbs
37881	33x12.50R15/C 108R	Standard	RWL	//	8.5" - 11"	12.5" on 10"	32.5"	640	15.0	2205@35	57.56 lbs
91644	34x10.50R17/D 120R	Standard	RWL	//	7" - 9"	10.6" on 8.5"	33.5"	621	15.0	3085@65	54.85 lbs
36312	34x12.50R18/E 121R	Standard	BSW	//	8.5" - 11"	12.5" on 10"	33.5"	621	15.0	3195@65	63.49 lbs
33572	35x12.50R15/C 113Q	Standard	RWL	//	8.5" - 11"	12.5" on 10"	34.5"	602	15.0	2535@35	64.04 lbs
66539	35x12.50R17/E 121R	Standard	RWL	//	8.5" - 11"	12.5" on 10"	34.5"	602	15.0	3195@65	66.27 lbs
13389	35x12.50R18/E 123R	Standard	RWL	//	8.5" - 11"	12.5" on 10"	34.5"	602	15.0	3415@65	67.59 lbs
23413	35x12.50R20/E 121R	Standard	BSW	//	8.5" - 11"	12.5" on 10"	34.5"	602	15.0	3195@75	66.8 lbs
35666	37x12.50R17/D 124R	Standard	RWL	//	8.5" - 11"	12.5" on 10"	36.5"	569	15.0	3525@50	69.49 lbs
93878	LT215/65R16/D 103/100S	Standard	BSW	//	6" - 7.5"	8.7" on 6.5"	27.0"	770	13.0	1930@65	35.87 lbs
56039	LT215/70R16/C 100/97R	Standard	RWL	//	5.5" - 7"	8.7" on 6.5"	27.9"	746	15.0	1765@50	34.48 lbs
44092	LT215/75R15/C 100/97S	Standard	BSW	//	5.5" - 7"	8.5" on 6"	27.7"	751	15.0	1765@50	33.05 lbs
95341	LT225/65R17/D 107/103S	Standard	BSW	//	6" - 8"	9" on 6.5"	28.5"	730	13.0	2150@65	38.85 lbs
94668	LT225/70R16/C 102/99R	Standard	RWL	//	6" - 7"	9" on 6.5"	28.4"	732	15.0	1875@50	35.63 lbs
37527	LT225/75R16/E 115/112S	Standard	RWL	//	6" - 7"	8.8" on 6"	29.3"	710	15.0	2680@80	42.81 lbs
33403	LT235/70R16/C 104/101S	Standard	RWL	//	6" - 7.5"	9.5" on 7"	29.0"	718	15.0	1985@50	37.21 lbs
63647	LT235/75R15/C 104/101S	Standard	RWL	//	6" - 7"	9.3" on 6.5"	28.9"	721	15.0	1985@50	36.53 lbs
10158	LT235/80R17/E 120/117S	Standard	BSW	//	6" - 7.5"	9.3" on 6.5"	31.8"	654	15.0	3085@80	48.04 lbs
75445	LT235/85R16/E 120/116S	Standard	RWL	//	6" - 7.5"	9.3" on 6.5"	31.7"	656	15.0	3042@80	49.25 lbs
52433	LT245/65R17/D 111/108S	Standard	RWL	//	7" - 8"	9.8" on 7"	29.5"	704	13.0	2405@65	44.03 lbs
28855	LT245/70R16/D 113/110S	Standard	RWL	//	6.5" - 7"	9.8" on 7"	29.5"	704	15.0	2535@65	45.41 lbs

All Terrain T/A KO2 - part number	Tire Size, Load Index &Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
09666	LT245/70R17/E 119/116S	Standard	RWL	//	6.5" - 8"	9.8" on 7"	30.6"	681	15.0	3000@80	47.18 lbs
15477	LT245/75R16/E 120/116S	Standard	RWL	//	6.5" - 8"	9.8" on 7"	30.5"	683	15.0	3042@80	48.88 lbs
26470	LT245/75R17/E 121/118S	Standard	RWL	//	6.5" - 7.5"	9.8" on 7"	31.5"	660	15.0	3195@80	49.78 lbs
04785	LT255/55R18/D 109/105R	Standard	BSW	//	7" - 9"	10.4" on 8"	29.0"	717	13.0	2270@65	44.55 lbs
28221	LT255/65R17/D 114/110S	Standard	RWL	//	7" - 9"	10.2" on 7.5"	30.1"	691	15.0	2600@65	47.71 lbs
65289	LT255/70R16/E 120/117S	Standard	RWL	//	6.5" - 8"	10.2" on 7.5"	30.1"	691	15.0	3085@80	48.04 lbs
37495	LT255/70R17/E 121/118S	Standard	BSW	//	6.5" - 8.5"	10.2" on 7.5"	31.1"	669	15.0	3195@80	49.78 lbs
70539	LT255/70R18/D 117/114S	Standard	BSW	//	6.5" - 8.5"	10.2" on 7.5"	32.1"	648	15.0	2835@65	50.79 lbs
11450	LT255/75R17/C 111/108S	Standard	BSW	//	6.5" - 8.5"	10" on 7"	32.1"	649	15.0	2405@50	45.48 lbs
63681	LT265/60R18/E 119/116S	Standard	BSW	//	7.5" - 9.5"	10.7" on 8"	30.5"	682	15.0	3000@80	50.0 lbs
85528	LT265/60R20/E 121/118S	Standard	BSW	//	7.5" - 9.5"	10.7" on 8"	32.5"	640	15.0	3195@80	57.43 lbs
16681	LT265/65R17/E 120/117S	Standard	RWL	//	7.5" - 9.5"	10.7" on 8"	30.6"	681	15.0	3085@80	49.98 lbs
05260	LT265/65R18/E 122/119R	Standard	RWL	//	7.5" - 9.5"	10.7" on 8"	31.5"	659	15.0	3305@80	51.63 lbs
62023	LT265/70R16/E 121/118S	Standard	RWL	//	7" - 8.5"	10.7" on 8"	30.6"	679	15.0	3195@80	50.77 lbs
66255	LT265/70R17/C 112/109S	Standard	RWL	//	7" - 8.5"	10.7" on 8"	31.7"	657	15.0	2470@50	44.95 lbs
10892	LT265/70R17/C 112/109S	Standard	BSW	//	7" - 8.5"	10.7" on 8"	31.7"	657	15.0	2470@50	45.72 lbs
29668	LT265/70R17/E 121/118S	Standard	RWL	//	7" - 8.5"	10.7" on 8"	31.7"	657	15.0	3195@80	53.51 lbs
40855	LT265/70R18/E 124/121R	Standard	RWL	//	7" - 9"	10.7" on 8"	32.6"	637	15.0	3525@80	54.52 lbs
67179	LT265/75R16/E 123/120R	Standard	RWL	//	7" - 8"	10.5" on 7.5"	31.7"	657	15.0	3415@80	53.57 lbs
61764	LT275/55R20/D 115/112S	Standard	BSW	//	7.5" - 9.5"	11.2" on 8.5"	31.9"	652	15.0	2680@65	53.73 lbs
64811	LT275/60R20/D 119/116S	Standard	BSW	//	7.5" - 9.5"	11" on 8"	33.0"	630	15.0	3000@65	55.29 lbs
42347	LT275/65R17/E 121/118S	Standard	RWL	//	7.5" - 9.5"	11" on 8"	31.1"	669	15.0	3195@80	52.65 lbs
19463	LT275/65R18/E 123/120R	Standard	RWL	//	7.5" - 9"	11" on 8"	32.1"	648	15.0	3415@80	55.45 lbs
17764	LT275/65R20/E 126/123S	Standard	BSW	//	7.5" - 9.5"	11" on 8"	34.1"	610	15.0	3750@80	58.29 lbs

All Terrain T/A KO2 - part number	Tire Size, Load Index &Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
97884	LT275/70R16/D 119/116S	Standard	RWL	//	7" - 8.5"	11" on 8"	31.2"	667	15.0	3000@65	51.15 lbs
85924	LT275/70R17/E 121/118R	Standard	RWL	//	7" - 8.5"	11" on 8"	32.2"	646	15.0	3195@80	55.29 lbs
45062	LT275/70R18/E 125/122R	Standard	RWL	//	7" - 8.5"	11" on 8"	33.2"	627	15.0	3640@80	57.39 lbs
36614	LT285/55R20/D 117/114T	Standard	BSW	//	8" - 10"	11.7" on 9"	32.4"	643	15.0	2835@65	56.02 lbs
99506	LT285/60R18/D 118/115S	Standard	RWL	//	8" - 10"	11.5" on 8.5"	31.5"	661	15.0	2910@65	53.64 lbs
29598	LT285/60R20/E 125/122S	Standard	BSW	//	8" - 10"	11.5" on 8.5"	33.5"	622	15.0	3640@80	61.51 lbs
16168	LT285/65R18/E 125/122R	Standard	RWL	//	8" - 10"	11.5" on 8.5"	32.6"	639	15.0	3640@80	57.19 lbs
02279	LT285/65R20/E 127/124S	Standard	BSW	//	8" - 10"	11.5" on 8.5"	34.6"	602	15.0	3860@80	61.68 lbs
81501	LT285/70R17/C 116/113Q	Standard	BSW	//	7.5" - 9"	11.5" on 8.5"	32.8"	635	15.0	2755@50	50.33 lbs
99728	LT285/70R17/E 121/118R	Standard	RWL	//	7.5" - 9"	11.5" on 8.5"	32.8"	635	15.0	3195@80	58.16 lbs
05855	LT285/75R16/E 126/123R	Standard	RWL	//	7.5" - 9"	11.3" on 8"	32.8"	634	15.0	3750@80	58.69 lbs
74713	LT285/75R17/E 121/118S	Standard	BSW	//	7.5" - 9.5"	11.3" on 8"	33.9"	614	15.0	3195@80	60.89 lbs
99926	LT295/75R16/E 128/125R	Standard	RWL	//	7.5" - 9.5"	11.6" on 8"	33.4"	623	15.0	3970@80	61.4 lbs
15149	LT305/55R20/E 121/118S	Standard	BSW	//	8.5" - 11"	12.4" on 9.5"	33.2"	626	15.0	3195@65	60.67 lbs
00819	LT305/65R17/E 121/118R	Standard	RWL	//	8.5" - 11"	12.2" on 9"	32.6"	638	15.0	3195@65	59.55 lbs
07337	LT305/65R18/E 124/121R	Standard	BSW	//	8.5" - 11"	12.2" on 9"	33.6"	619	15.0	3525@65	62.41 lbs
34102	LT305/70R16/E 124/121R	Standard	RWL	//	8" - 9.5"	12.2" on 9"	32.8"	634	15.0	3525@65	61.27 lbs
58424	LT315/70R17/C 113/110S	Standard	BSW	//	8" - 11"	12.7" on 9.5"	34.4"	604	15.0	2535@45	64.4 lbs
08806	LT315/70R17/E 121/118S	Standard	BSW	//	8" - 11"	12.7" on 9.5"	34.4"	604	15.0	3195@65	64.46 lbs
50203	LT315/75R16/E 127/124R	Standard	RWL	//	8" - 11"	12.3" on 8.5"	34.6"	602	15.0	3860@65	66.14 lbs
12201	LT325/60R20/E 126/123S	Standard	BSW	//	9" - 12"	13" on 9.5"	35.4"	588	15.0	3750@75	69.18 lbs
01547	LT325/65R18/E 127/124R	Standard	RWL	//	9" - 12"	13" on 9.5"	34.6"	601	15.0	3860@65	66.82 lbs