

| All Terrain<br>T/A KO2 -<br>part<br>number | Tire Size, Load Index<br>& Speed Rating | Mileage<br>Warranty | Sidewall | UTQG<br>Tread,<br>UTQG<br>Traction,<br>UTQG<br>Temp | Rim Width<br>Range<br>(Min/Max) | Section<br>Width on<br>Measuring<br>Rim Width | Overall<br>Diameter | revs/mi | Tread<br>Depth (in<br>32nds) | Max Load,<br>Single (lb<br>@ PSI) | Tire<br>Weight |
|--|---|---------------------|----------|---|---------------------------------|---|---------------------|---------|------------------------------|-----------------------------------|----------------|
| 64055                                      | 30x9.50R15/C 104S                       | Standard            | RWL      | //  | 6.5" - 8.5"                     | 9.5" on 7.5"                                  | 29.5"               | 705     | 15.0                         | 1990@50                           | 39.66 lbs      |
| 69948                                      | 31x10.50R15/C 109S                      | Standard            | RWL      | //  | 7" - 9"                         | 10.6" on 8.5"                                 | 30.5"               | 682     | 15.0                         | 2270@50                           | 43.96 lbs      |
| 13079                                      | 32x11.50R15/C 113R                      | Standard            | RWL      | //  | 8" - 10"                        | 11.4" on 9"                                   | 31.5"               | 659     | 15.0                         | 2535@50                           | 49.18 lbs      |
| 11548                                      | 33x10.50R15/C 114R                      | Standard            | RWL      | //  | 7" - 9"                         | 10.6" on 8.5"                                 | 32.5"               | 640     | 15.0                         | 2600@50                           | 51.06 lbs      |
| 37881                                      | 33x12.50R15/C 108R                      | Standard            | RWL      | //  | 8.5" - 11"                      | 12.5" on 10"                                  | 32.5"               | 640     | 15.0                         | 2205@35                           | 57.58 lbs      |
| 91644                                      | 34x10.50R17/D 120R                      | Standard            | RWL      | //  | 7" - 9"                         | 10.6" on 8.5"                                 | 33.5"               | 621     | 15.0                         | 3085@65                           | 54.85 lbs      |
| 36312                                      | 34x12.50R18/E 121R                      | Standard            | BSW      | //  | 8.5" - 11"                      | 12.5" on 10"                                  | 33.5"               | 621     | 15.0                         | 3195@65                           | 63.47 lbs      |
| 33572                                      | 35x12.50R15/C 113Q                      | Standard            | RWL      | //  | 8.5" - 11"                      | 12.5" on 10"                                  | 34.5"               | 602     | 15.0                         | 2535@35                           | 64.04 lbs      |
| 66539                                      | 35x12.50R17/E 121R                      | Standard            | RWL      | //  | 8.5" - 11"                      | 12.5" on 10"                                  | 34.5"               | 602     | 15.0                         | 3195@65                           | 66.27 lbs      |
| 13389                                      | 35x12.50R18/E 123R                      | Standard            | RWL      | //  | 8.5" - 11"                      | 12.5" on 10"                                  | 34.5"               | 602     | 15.0                         | 3415@65                           | 67.59 lbs      |
| 23413                                      | 35x12.50R20/E 121R                      | Standard            | BSW      | //  | 8.5" - 11"                      | 12.5" on 10"                                  | 34.5"               | 602     | 15.0                         | 3195@75                           | 66.49 lbs      |
| 35666                                      | 37x12.50R17/D 124R                      | Standard            | RWL      | //  | 8.5" - 11"                      | 12.5" on 10"                                  | 36.5"               | 569     | 15.0                         | 3525@50                           | 69.49 lbs      |
| 93878                                      | LT215/65R16/D 103/100S                  | Standard            | BSW      | //  | 6" - 7.5"                       | 8.7" on 6.5"                                  | 27.0"               | 770     | 13.0                         | 1930@65                           | 35.85 lbs      |
| 56039                                      | LT215/70R16/C 100/97R                   | Standard            | RWL      | //  | 5.5" - 7"                       | 8.7" on 6.5"                                  | 27.9"               | 746     | 15.0                         | 1765@50                           | 34.48 lbs      |
| 44092                                      | LT215/75R15/C 100/97S                   | Standard            | BSW      | //  | 5.5" - 7"                       | 8.5" on 6"                                    | 27.7"               | 751     | 15.0                         | 1765@50                           | 33.09 lbs      |
| 95341                                      | LT225/65R17/D 107/103S                  | Standard            | BSW      | //  | 6" - 8"                         | 9" on 6.5"                                    | 28.5"               | 730     | 13.0                         | 2150@65                           | 39.66 lbs      |
| 94668                                      | LT225/70R16/C 102/99R                   | Standard            | RWL      | //  | 6" - 7"                         | 9" on 6.5"                                    | 28.4"               | 732     | 15.0                         | 1875@50                           | 35.69 lbs      |
| 37527                                      | LT225/75R16/E 115/112S                  | Standard            | RWL      | //  | 6" - 7"                         | 8.8" on 6"                                    | 29.3"               | 710     | 15.0                         | 2680@80                           | 42.79 lbs      |
| 33403                                      | LT235/70R16/C 104/101S                  | Standard            | RWL      | //  | 6" - 7.5"                       | 9.5" on 7"                                    | 29.0"               | 718     | 15.0                         | 1985@50                           | 37.24 lbs      |
| 63647                                      | LT235/75R15/C 104/101S                  | Standard            | RWL      | //  | 6" - 7"                         | 9.3" on 6.5"                                  | 28.9"               | 721     | 15.0                         | 1985@50                           | 36.53 lbs      |
| 10158                                      | LT235/80R17/E 120/117S                  | Standard            | BSW      | //  | 6" - 7.5"                       | 9.3" on 6.5"                                  | 31.8"               | 654     | 15.0                         | 3085@80                           | 47.97 lbs      |
| 75445                                      | LT235/85R16/E 120/116S                  | Standard            | RWL      | //  | 6" - 7.5"                       | 9.3" on 6.5"                                  | 31.7"               | 656     | 15.0                         | 3042@80                           | 50.24 lbs      |
| 52433                                      | LT245/65R17/D 111/108S                  | Standard            | RWL      | //  | 7" - 8"                         | 9.8" on 7"                                    | 29.5"               | 704     | 13.0                         | 2405@65                           | 44.75 lbs      |
| 28855                                      | LT245/70R16/D 113/110S                  | Standard            | RWL      | //  | 6.5" - 7"                       | 9.8" on 7"                                    | 29.5"               | 704     | 15.0                         | 2535@65                           | 45.37 lbs      |

| All Terrain<br>T/A KO2 -<br>part<br>number | Tire Size, Load Index<br>& Speed Rating | Mileage<br>Warranty | Sidewall | UTQG<br>Tread,<br>UTQG<br>Traction,<br>UTQG<br>Temp | Rim Width<br>Range<br>(Min/Max) | Section<br>Width on<br>Measuring<br>Rim Width | Overall<br>Diameter | revs/mi | Tread<br>Depth (in<br>32nds) | Max Load,<br>Single (lb<br>@ PSI) | Tire<br>Weight |
|--|---|---------------------|----------|---|---------------------------------|---|---------------------|---------|------------------------------|-----------------------------------|----------------|
| 09666                                      | LT245/70R17/E 119/116S                  | Standard            | RWL      | //  | 6.5" - 8"                       | 9.8" on 7"                                    | 30.6"               | 681     | 15.0                         | 3000@80                           | 47.18 lbs      |
| 15477                                      | LT245/75R16/E 120/116S                  | Standard            | RWL      | //  | 6.5" - 8"                       | 9.8" on 7"                                    | 30.5"               | 683     | 15.0                         | 3042@80                           | 48.81 lbs      |
| 26470                                      | LT245/75R17/E 121/118S                  | Standard            | RWL      | //  | 6.5" - 7.5"                     | 9.8" on 7"                                    | 31.5"               | 660     | 15.0                         | 3195@80                           | 49.74 lbs      |
| 04785                                      | LT255/55R18/D 109/105R                  | Standard            | RBL      | //  | 7" - 9"                         | 10.4" on 8"                                   | 29.0"               | 717     | 13.0                         | 2270@65                           | 44.55 lbs      |
| 28221                                      | LT255/65R17/D 114/110S                  | Standard            | RWL      | //  | 7" - 9"                         | 10.2" on 7.5"                                 | 30.1"               | 691     | 15.0                         | 2600@65                           | 47.71 lbs      |
| 65289                                      | LT255/70R16/E 120/117S                  | Standard            | RWL      | //  | 6.5" - 8"                       | 10.2" on 7.5"                                 | 30.1"               | 691     | 15.0                         | 3085@80                           | 48.28 lbs      |
| 37495                                      | LT255/70R17/E 121/118S                  | Standard            | BSW      | //  | 6.5" - 8.5"                     | 10.2" on 7.5"                                 | 31.1"               | 669     | 15.0                         | 3195@80                           | 49.71 lbs      |
| 70539                                      | LT255/70R18/D 117/114S                  | Standard            | BSW      | //  | 6.5" - 8.5"                     | 10.2" on 7.5"                                 | 32.1"               | 648     | 15.0                         | 2835@65                           | 50.79 lbs      |
| 11450                                      | LT255/75R17/C 111/108S                  | Standard            | BSW      | //  | 6.5" - 8.5"                     | 10" on 7"                                     | 32.1"               | 649     | 15.0                         | 2405@50                           | 45.48 lbs      |
| 63681                                      | LT265/60R18/E 119/116S                  | Standard            | BSW      | //  | 7.5" - 9.5"                     | 10.7" on 8"                                   | 30.5"               | 682     | 15.0                         | 3000@80                           | 50.0 lbs       |
| 85528                                      | LT265/60R20/E 121/118S                  | Standard            | BSW      | //  | 7.5" - 9.5"                     | 10.7" on 8"                                   | 32.5"               | 640     | 15.0                         | 3195@80                           | 57.39 lbs      |
| 16681                                      | LT265/65R17/E 120/117S                  | Standard            | RWL      | //  | 7.5" - 9.5"                     | 10.7" on 8"                                   | 30.6"               | 681     | 15.0                         | 3085@80                           | 50.0 lbs       |
| 05260                                      | LT265/65R18/E 122/119R                  | Standard            | RWL      | //  | 7.5" - 9.5"                     | 10.7" on 8"                                   | 31.5"               | 659     | 15.0                         | 3305@80                           | 51.5 lbs       |
| 62023                                      | LT265/70R16/E 121/118S                  | Standard            | RWL      | //  | 7" - 8.5"                       | 10.7" on 8"                                   | 30.6"               | 679     | 15.0                         | 3195@80                           | 51.46 lbs      |
| 66255                                      | LT265/70R17/C 112/109S                  | Standard            | RWL      | //  | 7" - 8.5"                       | 10.7" on 8"                                   | 31.7"               | 657     | 15.0                         | 2470@50                           | 45.17 lbs      |
| 10892                                      | LT265/70R17/C 112/109S                  | Standard            | BSW      | //  | 7" - 8.5"                       | 10.7" on 8"                                   | 31.7"               | 657     | 15.0                         | 2470@50                           | 45.5 lbs       |
| 29668                                      | LT265/70R17/E 121/118S                  | Standard            | RWL      | //  | 7" - 8.5"                       | 10.7" on 8"                                   | 31.7"               | 657     | 15.0                         | 3195@80                           | 53.37 lbs      |
| 40855                                      | LT265/70R18/E 124/121R                  | Standard            | RWL      | //  | 7" - 9"                         | 10.7" on 8"                                   | 32.6"               | 637     | 15.0                         | 3525@80                           | 54.52 lbs      |
| 42353                                      | LT265/75R16/E 123/120R                  | 50,000 Mile         | RWL      | //  | 7" - 8"                         | 10.5" on 7.5"                                 | 31.7"               | 657     | 15.0                         | 3415@80                           | 54.32 lbs      |
| 67179                                      | LT265/75R16/E 123/120R                  | Standard            | RWL      | //  | 7" - 8"                         | 10.5" on 7.5"                                 | 31.7"               | 657     | 15.0                         | 3415@80                           | 53.97 lbs      |
| 61764                                      | LT275/55R20/D 115/112S                  | Standard            | RBL      | //  | 7.5" - 9.5"                     | 11.2" on 8.5"                                 | 31.9"               | 652     | 15.0                         | 2680@65                           | 54.76 lbs      |
| 64811                                      | LT275/60R20/D 119/116S                  | Standard            | BSW      | //  | 7.5" - 9.5"                     | 11" on 8"                                     | 33.0"               | 630     | 15.0                         | 3000@65                           | 55.29 lbs      |
| 42347                                      | LT275/65R17/E 121/118S                  | Standard            | RWL      | //  | 7.5" - 9.5"                     | 11" on 8"                                     | 31.1"               | 669     | 15.0                         | 3195@80                           | 52.07 lbs      |
| 19463                                      | LT275/65R18/E 123/120R                  | Standard            | RWL      | //  | 7.5" - 9"                       | 11" on 8"                                     | 32.1"               | 648     | 15.0                         | 3415@80                           | 55.53 lbs      |

| All Terrain<br>T/A KO2 -<br>part<br>number | Tire Size, Load Index<br>& Speed Rating | Mileage<br>Warranty | Sidewall | UTQG<br>Tread,<br>UTQG<br>Traction,<br>UTQG<br>Temp | Rim Width<br>Range<br>(Min/Max) | Section<br>Width on<br>Measuring<br>Rim Width | Overall<br>Diameter | revs/mi | Tread<br>Depth (in<br>32nds) | Max Load,<br>Single (lb<br>@ PSI) | Tire<br>Weight |
|--|---|---------------------|----------|---|---------------------------------|---|---------------------|---------|------------------------------|-----------------------------------|----------------|
| 16152                                      | LT275/65R20/E 126/123S                  | 50,000 Mile         | BSW      | //  | 7.5" - 9.5"                     | 11" on 8"                                     | 34.1"               | 610     | 15.0                         | 3750@80                           | 57.87 lbs      |
| 17764                                      | LT275/65R20/E 126/123S                  | Standard            | BSW      | //  | 7.5" - 9.5"                     | 11" on 8"                                     | 34.1"               | 610     | 15.0                         | 3750@80                           | 58.27 lbs      |
| 97884                                      | LT275/70R16/D 119/116S                  | Standard            | RWL      | //  | 7" - 8.5"                       | 11" on 8"                                     | 31.2"               | 667     | 15.0                         | 3000@65                           | 51.1 lbs       |
| 85924                                      | LT275/70R17/E 121/118R                  | Standard            | RWL      | //  | 7" - 8.5"                       | 11" on 8"                                     | 32.2"               | 646     | 15.0                         | 3195@80                           | 55.31 lbs      |
| 23104                                      | LT275/70R18/E 125/122R                  | 50,000 Mile         | RWL      | //  | 7" - 8.5"                       | 11" on 8"                                     | 33.2"               | 627     | 15.0                         | 3640@80                           | 58.77 lbs      |
| 45062                                      | LT275/70R18/E 125/122R                  | Standard            | RWL      | //  | 7" - 8.5"                       | 11" on 8"                                     | 33.2"               | 627     | 15.0                         | 3640@80                           | 57.39 lbs      |
| 36614                                      | LT285/55R20/D 117/114T                  | Standard            | RBL      | //  | 8" - 10"                        | 11.7" on 9"                                   | 32.4"               | 643     | 15.0                         | 2835@65                           | 56.02 lbs      |
| 99506                                      | LT285/60R18/D 118/115S                  | Standard            | RWL      | //  | 8" - 10"                        | 11.5" on 8.5"                                 | 31.5"               | 661     | 15.0                         | 2910@65                           | 54.34 lbs      |
| 29598                                      | LT285/60R20/E 125/122S                  | Standard            | BSW      | //  | 8" - 10"                        | 11.5" on 8.5"                                 | 33.5"               | 622     | 15.0                         | 3640@80                           | 61.42 lbs      |
| 16168                                      | LT285/65R18/E 125/122R                  | Standard            | RWL      | //  | 8" - 10"                        | 11.5" on 8.5"                                 | 32.6"               | 639     | 15.0                         | 3640@80                           | 57.21 lbs      |
| 88846                                      | LT285/65R20/E 127/124S                  | 50,000 Mile         | BSW      | //  | 8" - 10"                        | 11.5" on 8.5"                                 | 34.6"               | 602     | 15.0                         | 3860@80                           | 62.37 lbs      |
| 02279                                      | LT285/65R20/E 127/124S                  | Standard            | RBL      | //  | 8" - 10"                        | 11.5" on 8.5"                                 | 34.6"               | 602     | 15.0                         | 3860@80                           | 61.71 lbs      |
| 31812                                      | LT285/70R17/C 116/113Q                  | Standard            | RWL      | //  | 7.5" - 9"                       | 11.5" on 8.5"                                 | 32.8"               | 635     | 15.0                         | 2755@50                           | 51.37 lbs      |
| 81501                                      | LT285/70R17/C 116/113Q                  | Standard            | RBL      | //  | 7.5" - 9"                       | 11.5" on 8.5"                                 | 32.8"               | 635     | 15.0                         | 2755@50                           | 50.33 lbs      |
| 89442                                      | LT285/70R17/E 121/118R                  | 50,000 Mile         | RWL      | //  | 7.5" - 9"                       | 11.5" on 8.5"                                 | 32.8"               | 635     | 15.0                         | 3195@80                           | 57.87 lbs      |
| 99728                                      | LT285/70R17/E 121/118R                  | Standard            | RWL      | //  | 7.5" - 9"                       | 11.5" on 8.5"                                 | 32.8"               | 635     | 15.0                         | 3195@80                           | 58.11 lbs      |
| 72596                                      | LT285/75R16/E 126/123R                  | 50,000 Mile         | RWL      | //  | 7.5" - 9"                       | 11.3" on 8"                                   | 32.8"               | 634     | 15.0                         | 3750@80                           | 59.0 lbs       |
| 05855                                      | LT285/75R16/E 126/123R                  | Standard            | RWL      | //  | 7.5" - 9"                       | 11.3" on 8"                                   | 32.8"               | 634     | 15.0                         | 3750@80                           | 58.69 lbs      |
| 74713                                      | LT285/75R17/E 121/118S                  | Standard            | BSW      | //  | 7.5" - 9.5"                     | 11.3" on 8"                                   | 33.9"               | 614     | 15.0                         | 3195@80                           | 60.89 lbs      |
| 99926                                      | LT295/75R16/E 128/125R                  | Standard            | RWL      | //  | 7.5" - 9.5"                     | 11.6" on 8"                                   | 33.4"               | 623     | 15.0                         | 3970@80                           | 61.4 lbs       |
| 15149                                      | LT305/55R20/E 121/118S                  | Standard            | RBL      | //  | 8.5" - 11"                      | 12.4" on 9.5"                                 | 33.2"               | 626     | 15.0                         | 3195@65                           | 60.76 lbs      |
| 00819                                      | LT305/65R17/E 121/118R                  | Standard            | RWL      | //  | 8.5" - 11"                      | 12.2" on 9"                                   | 32.6"               | 638     | 15.0                         | 3195@65                           | 59.55 lbs      |
| 07337                                      | LT305/65R18/E 124/121R                  | Standard            | RBL      | //  | 8.5" - 11"                      | 12.2" on 9"                                   | 33.6"               | 619     | 15.0                         | 3525@65                           | 62.3 lbs       |
| 34102                                      | LT305/70R16/E 124/121R                  | Standard            | RWL      | //  | 8" - 9.5"                       | 12.2" on 9"                                   | 32.8"               | 634     | 15.0                         | 3525@65                           | 61.09 lbs      |

| All Terrain<br>T/A KO2 -<br>part<br>number | Tire Size, Load Index<br>& Speed Rating | Mileage<br>Warranty | Sidewall | UTQG<br>Tread,<br>UTQG<br>Traction,<br>UTQG<br>Temp | Rim Width<br>Range<br>(Min/Max) | Section<br>Width on<br>Measuring<br>Rim Width | Overall<br>Diameter | revs/mi | Tread<br>Depth (in<br>32nds) | Max Load,<br>Single (lb<br>@ PSI) | Tire<br>Weight |
|--|---|---------------------|----------|---|---------------------------------|---|---------------------|---------|------------------------------|-----------------------------------|----------------|
| 58424                                      | LT315/70R17/C 113/110S                  | Standard            | BSW      | //  | 8" - 11"                        | 12.7" on 9.5"                                 | 34.4"               | 604     | 15.0                         | 2535@45                           | 64.4 lbs       |
| 08806                                      | LT315/70R17/E 121/118S                  | Standard            | BSW      | //  | 8" - 11"                        | 12.7" on 9.5"                                 | 34.4"               | 604     | 15.0                         | 3195@65                           | 64.59 lbs      |
| 50203                                      | LT315/75R16/E 127/124R                  | Standard            | RWL      | //  | 8" - 11"                        | 12.3" on 8.5"                                 | 34.6"               | 602     | 15.0                         | 3860@65                           | 66.16 lbs      |
| 12201                                      | LT325/60R20/E 126/123S                  | Standard            | RBL      | //  | 9" - 12"                        | 13" on 9.5"                                   | 35.4"               | 588     | 15.0                         | 3750@75                           | 69.18 lbs      |
| 01547                                      | LT325/65R18/E 127/124R                  | Standard            | RWL      | //  | 9" - 12"                        | 13" on 9.5"                                   | 34.6"               | 601     | 15.0                         | 3860@65                           | 66.84 lbs      |