

g-Force COMP-2 A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
06908	205/45ZR16/XL 87W	45,000 Mile	BSW	400/AA/A	6.5" - 7.5"	8.11" on 7"	23.23"	895	9.0	1201@50	22.46 lbs
00924	205/45ZR17/XL 88W	45,000 Mile	BSW	400/AA/A	6.5" - 7.5"	8.11" on 7"	24.25"	858	9.0	1235@50	22.22 lbs
27889	205/50ZR16 87W	45,000 Mile	BSW	400/AA/A	5.5" - 7.5"	8.43" on 6.5"	24.09"	863	9.0	1201@51	22.38 lbs
31113	205/50ZR17/XL 93W	45,000 Mile	BSW	400/AA/A	5.5" - 7.5"	8.43" on 6.5"	25.12"	828	9.0	1433@50	23.79 lbs
36969	205/55ZR16 91W	45,000 Mile	BSW	400/AA/A	5.5" - 7.5"	8.43" on 6.5"	24.88"	836	9.0	1356@51	23.72 lbs
19100	215/45ZR17/XL 91W	45,000 Mile	BSW	400/AA/A	7" - 8"	8.39" on 7"	24.65"	844	9.0	1356@50	23.02 lbs
46035	215/45ZR18/XL 93W	45,000 Mile	BSW	400/AA/A	7" - 8"	8.39" on 7"	25.63"	812	9.0	1433@50	24.12 lbs
13715	215/50ZR17/XL 95W	45,000 Mile	BSW	400/AA/A	6" - 7.5"	8.9" on 7"	25.51"	815	9.0	1521@50	25.04 lbs
29016	215/55ZR17 94W	45,000 Mile	BSW	400/AA/A	6" - 7.5"	8.9" on 7"	26.3"	791	9.0	1477@51	25.62 lbs
70191	225/40ZR18/XL 92W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.06" on 8"	25.08"	829	9.0	1389@50	24.58 lbs
56599	225/40ZR19/XL 93W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.06" on 8"	26.1"	797	9.0	1433@50	25.71 lbs
37942	225/45ZR17/XL 94W	45,000 Mile	BSW	400/AA/A	7" - 8.5"	8.86" on 7.5"	24.96"	833	9.0	1477@50	24.23 lbs
04031	225/45ZR18/XL 95W	45,000 Mile	BSW	400/AA/A	7" - 8.5"	8.86" on 7.5"	25.94"	802	9.0	1521@50	25.09 lbs
81545	225/45ZR19 92W	45,000 Mile	BSW	400/AA/A	7" - 8.5"	8.86" on 7.5"	26.97"	771	9.0	1389@51	26.63 lbs
37570	225/50ZR16 92W	45,000 Mile	BSW	400/AA/A	6" - 8"	9.17" on 7"	24.88"	836	9.0	1389@51	25.53 lbs
17354	225/50ZR17 94W	45,000 Mile	BSW	400/AA/A	6" - 8"	9.17" on 7"	25.91"	803	9.0	1477@51	26.54 lbs
45091	225/50ZR18 95W	45,000 Mile	BSW	400/AA/A	6" - 8"	9.17" on 7"	26.89"	774	9.0	1521@51	27.82 lbs
03897	225/55ZR16 95W	45,000 Mile	BSW	400/AA/A	6" - 8"	9.17" on 7"	25.75"	808	9.0	1521@51	26.15 lbs
60444	225/55ZR17 97W	45,000 Mile	BSW	400/AA/A	6" - 8"	9.17" on 7"	26.77"	777	9.0	1609@51	27.36 lbs
08126	235/40ZR18/XL 95W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.49" on 8.5"	25.39"	819	9.0	1521@50	25.88 lbs
87971	235/45ZR17/XL 97W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.29" on 8"	25.35"	821	9.0	1609@50	25.57 lbs
61946	235/45ZR18/XL 98W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.29" on 8"	26.34"	790	9.0	1653@50	26.65 lbs
27274	235/50ZR17 96W	45,000 Mile	BSW	400/AA/A	6.5" - 8.5"	9.65" on 7.5"	26.3"	791	9.0	1565@51	28.92 lbs
20279	235/50ZR18 97W	45,000 Mile	BSW	400/AA/A	6.5" - 8.5"	9.65" on 7.5"	27.28"	762	9.0	1609@51	29.39 lbs

g-Force COMP-2 A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
29901	235/55ZR17 99W	45,000 Mile	BSW	400/AA/A	6.5" - 8.5"	9.65" on 7.5"	27.17"	766	9.0	1709@51	30.27 lbs
24467	245/35ZR19/XL 93W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.76" on 8.5"	25.79"	807	9.0	1433@50	27.84 lbs
62252	245/35ZR20/XL 95W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.76" on 8.5"	26.77"	777	9.0	1521@50	28.68 lbs
24965	245/40ZR17 91W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.76" on 8.5"	24.72"	841	9.0	1356@51	25.75 lbs
80886	245/40ZR18/XL 97W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.76" on 8.5"	25.71"	809	9.0	1609@50	26.85 lbs
05226	245/40ZR18/XL 97Y	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.76" on 8.5"	25.71"	809	9.0	1609@50	26.85 lbs
77099	245/40ZR19 94W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.76" on 8.5"	26.73"	778	9.0	1477@51	28.17 lbs
32583	245/40ZR20/XL 99W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	9.76" on 8.5"	27.72"	750	9.0	1709@50	28.86 lbs
18621	245/45ZR17/XL 99W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.57" on 8"	25.67"	810	9.0	1709@50	26.81 lbs
38853	245/45ZR18 96W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.57" on 8"	26.65"	780	9.0	1565@51	28.06 lbs
38110	245/45ZR19 98W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.57" on 8"	27.68"	751	9.0	1653@51	29.32 lbs
46912	245/45ZR20/XL 103W	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.57" on 8"	28.66"	726	9.0	1930@50	31.31 lbs
20491	245/45ZR20/XL 103Y	45,000 Mile	BSW	400/AA/A	7.5" - 9"	9.57" on 8"	28.66"	726	9.0	1929@50	30.49 lbs
65801	245/50ZR16 97W	45,000 Mile	BSW	400/AA/A	7" - 8.5"	9.96" on 7.5"	25.67"	810	9.0	1609@51	27.84 lbs
08793	245/50ZR19/XL 105W	45,000 Mile	BSW	400/AA/A	7" - 8.5"	9.96" on 7.5"	28.7"	725	9.0	2041@50	33.73 lbs
77984	255/35ZR18/XL 94W	45,000 Mile	BSW	400/AA/A	8.5" - 10"	10.24" on 9"	25.0"	832	9.0	1477@50	27.34 lbs
24235	255/35ZR19/XL 96W	45,000 Mile	BSW	400/AA/A	8.5" - 10"	10.24" on 9"	26.02"	799	9.0	1565@50	29.83 lbs
30376	255/35ZR20/XL 97W	45,000 Mile	BSW	400/AA/A	8.5" - 10"	10.24" on 9"	27.01"	770	9.0	1609@50	29.81 lbs
14143	255/40ZR17 94W	45,000 Mile	BSW	400/AA/A	8.5" - 10"	10.24" on 9"	25.04"	831	9.0	1477@51	26.76 lbs
60347	255/40ZR18/XL 99W	45,000 Mile	BSW	400/AA/A	8.5" - 10"	10.24" on 9"	26.02"	799	9.0	1709@50	27.89 lbs
89100	255/40ZR19/XL 100W	45,000 Mile	BSW	400/AA/A	8.5" - 10"	10.24" on 9"	27.05"	769	9.0	1764@50	31.86 lbs
92946	255/40ZR19/XL 100Y	45,000 Mile	BSW	400/AA/A	8.5" - 10"	10.24" on 9"	27.05"	769	9.0	1764@50	32.74 lbs
15054	255/45ZR18 99W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	10.04" on 8.5"	27.05"	769	9.0	1709@51	28.55 lbs

g-Force COMP-2 A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
94555	255/45ZR20 101W	45,000 Mile	BSW	400/AA/A	8" - 9.5"	10.04" on 8.5"	29.06"	716	9.0	1819@51	31.9 lbs
35709	265/35ZR18/XL 97W	45,000 Mile	BSW	400/AA/A	9" - 10.5"	10.67" on 9.5"	25.31"	822	9.0	1609@50	27.49 lbs
79669	275/35ZR18 95W	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	25.55"	814	9.0	1521@51	28.44 lbs
04801	275/35ZR19 96W	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	26.57"	783	9.0	1565@51	30.69 lbs
19943	275/35ZR20/XL 102W	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	27.56"	755	9.0	1874@50	31.64 lbs
21945	275/40ZR17 98W	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	25.67"	810	9.0	1653@51	29.19 lbs
56680	275/40ZR18 99W	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	26.65"	780	9.0	1709@51	30.45 lbs
27812	275/40ZR19 101W	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	27.68"	751	9.0	1819@51	31.92 lbs
11108	275/40ZR20/XL 106W	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	28.66"	726	9.0	2094@50	34.48 lbs
91904	275/40ZR20/XL 106Y	45,000 Mile	BSW	400/AA/A	9" - 11"	10.94" on 9.5"	28.66"	726	9.0	2094@50	35.21 lbs
73542	285/35ZR19/XL 103W	45,000 Mile	BSW	400/AA/A	9.5" - 11"	11.42" on 10"	26.89"	774	9.0	1930@50	32.39 lbs
11292	285/35ZR19/XL 103Y	45,000 Mile	BSW	400/AA/A	9.5" - 11"	11.42" on 10"	26.89"	774	9.0	1929@50	33.36 lbs

g-Force COMP-2 A/S - part number	Tire Size, Load Index & Speed Rating	Mileage Warranty	Sidewall	UTQG Tread, UTQG Traction, UTQG Temp	Rim Width Range (Min/Max)	Section Width on Measuring Rim Width	Overall Diameter	revs/mi	Tread Depth (in 32nds)	Max Load, Single (lb @ PSI)	Tire Weight
09693	285/35ZR20 100W	45,000 Mile	BSW	400/AA/A	9.5" - 11"	11.42" on 10"	27.87"	746	9.0	1764@51	32.94 lbs
20717	285/35ZR20 100Y	45,000 Mile	BSW	400/AA/A	9.5" - 11"	11.42" on 10"	27.87"	746	9.0	1764@51	32.43 lbs
04642	305/35ZR20 104W	45,000 Mile	BSW	400/AA/A	10" - 12"	12.32" on 11"	28.43"	732	9.0	1984@51	38.16 lbs
32255	305/35ZR20 104Y	45,000 Mile	BSW	400/AA/A	10" - 12"	12.32" on 11"	28.43"	732	9.0	1984@51	38.29 lbs